



# TWO WAY RADIOS UK

[HTTPS://TWOWAYRADIOSUK.CO.UK](https://twowayradiosuk.co.uk)

01782537000

**Hytera**  
Respond & Achieve



## P3D Series DMR handheld radios

The P3D series from Hytera offers you business radios in pocket format. The compact design and intuitive operation make these DMR handheld radios your companion for reliable digital radio communication.



**DMR**  
DIGITAL MOBILE RADIO ASSOCIATION



# TWO WAY RADIOS UK

[HTTPS://TWOWAYRADIOSUK.CO.UK](https://twowayradiosuk.co.uk)

01782537000

# Radios

## P3D Series

P3D55

P3D65

P3D75

DMR handheld radios



### Highlights

#### Digital mobile radio never looked so good

The radios of the P3D series excel through their stylish and compact design in smartphone format and their intuitive operation. With a weight of only 160 g (P3D55/P3D65) and 165 g (P3D75), they can be carried conveniently even on long working days.

#### Support of analog and digital mobile radio

The P3D series was developed in compliance with the ETSI mobile radio standard Digital Mobile Radio (DMR). The handheld radios support the conventional DMR operation and can also be operated in analog mode.

#### Expanded frequency range (P3D75)

The P3D75 expands Hytera's PD3 series by a larger frequency range. It operates in the UHF band between 400 – 450 MHz or 430 – 480 MHz.

#### Integrated antenna design

The unique integrated antenna design enables excellent availability without a large antenna on the radio.

#### Affordable pricing

The terminals of the P3D series offer not only many functions, but also a quick, no-nonsense start into digital mobile radio at a fair price.

#### Long battery service life

The lithium-ion batteries (2000 mAh) included in the delivery enable the P3D handheld radios to achieve an operating time of at least 12 hours in digital mode, with a duty cycle of 5-5-90.

#### Additional Functions (selection)

- Selectable transmitting power: 1.5 W or 3 W
- Analog signaling: CTCSS, CDCSS
- Protection against dust and moisture according to IP54
- Shock and vibration resistance according to MIL-STD-810 C/D/E/F/G
- DMR text messages with up to 64 characters
- Four programmable keys
- Charging and programming via Micro-USB interface
- Scan function for analog and digital channels
- Versatile voice calls: Individual call, group call, and broadcast call on digital channels



TWO WAY RADIOS UK

[HTTPS://TWOWAYRADIOSUK.CO.UK](https://twowayradiosuk.co.uk)

01782537000



Micro-USB port for charging and programming

Integrated antenna design



Compact design and easily readable display

Programmable keys

Expanded frequency range in the UHF band at 400 – 450 MHz or at 430 – 480 MHz (PD375)

**Standard scope of delivery**

**Additional accessories (selection)**



Lithium-ion battery (2000 mAh) BL2009



EU power supply unit for Micro-USB PS1029



Programming cable USB PC69



Earphone with C-clip EH516



Hand strap (Nylon) RO01



Belt clip suitable for the radio

## Technical Data

General data	
<b>Frequency range</b> P3D55 / P3D65 P3D75	UHF: 400 – 440 MHz, 430 – 470 MHz UHF: 400 – 450 MHz, 430 – 480 MHz
Supported operating modes	<ul style="list-style-type: none"> <li>DMR Tier II in acc. with ETSI TS 102 361-1/2/3</li> <li>Analog</li> </ul>
Channel capacity	256 (128 analog + 128 digital)
Number of zones	16
Channel spacing	12.5 / 25 kHz (analog) 12.5 kHz (digital)
Operating voltage	3.7V (nominal)
Standard battery	2000 mAh (lithium-ion battery)
Battery service life (5-5-90 duty cycle, high transmitting power, standard battery)	approx. 10 hours (analog) approx. 12 hours (digital)
Frequency stability	± 0.5 ppm
Antenna impedance	50 Ω
Dimensions (H × B × T)	123 × 58 × 23 mm (PD355) 135 × 58 × 24 mm (PD365) 140 × 54 × 23 mm (PD375)
Weight (with antenna and standard battery)	approx. 160 g (PD355/PD365) approx. 165 g (PD375)
Display	monochrome LC display, 3 lines

Environmental conditions	
Operating temperature range	- 30 °C to + 60 °C
Storage temperature range	- 40 °C to + 85 °C
ESD	IEC 61000-4-2 (Level 4), ± 8 kV (contact), ± 15 kV (air)
Protection against dust and moisture	IP54
Shock and vibration resistance	MIL-STD-810 C/D/E/F/G
Relative humidity	MIL-STD-810 C/D/E/F/G

Transmitter	
Transmitting power	UHF: 1.5/3 W
Modulation	11 K0F3E at 12.5 kHz 16 K0F3E at 25 kHz
4FSK digital modulation	12.5 kHz (data only): 7K60FXD 12.5 kHz (data and voice): 7K60FXW
Interfering signals and harmonics	- 36 dBm (< 1 GHz) - 30 dBm (> 1 GHz)
Modulation limiting	± 2.5 kHz at 12.5 kHz ± 5.0 kHz at 25 kHz
Hum and noise	40 dB at 12.5 kHz 45 dB at 25 kHz
Adjacent channel selectivity	60 dB at 12.5 kHz 70 dB at 25 kHz
Audio sensitivity	+ 1 dB at - 3 dB
Audio distortion	° 3 %
Digital vocoder type	AMBE+2™

Receiver	
Sensitivity (analog)	0.22 , V (typical) (12 dB SINAD) 0.4 , V (20 dB SINAD) 0.22 , V (12 dB SINAD)
Sensitivity (digital)	0.22 , V / BER 5 %
<b>Adjacent channel selectivity</b> TIA-603 ETSI	60 dB at 12.5 kHz / 70 dB at 25 kHz 60 dB at 12.5 kHz / 70 dB at 25 kHz
<b>Intermodulation</b> TIA-603 ETSI	70 dB at 12.5 / 25 kHz 65 dB at 12.5 / 25 kHz
<b>Spurious response rejection</b> TIA-603 ETSI	70 dB at 12.5 / 25 kHz 70 dB at 12.5 / 25 kHz
Signal-noise ratio (S/N)	40 dB at 12.5 kHz 45 dB at 25 kHz
Audio power output	0.4 W
Audio distortion	° 5 %
Audio sensitivity	+ 1 dB at - 3 dB
Conducted spurious emission	< - 57 dBm

All technical information was determined at the factory and in accordance with the corresponding standards. Subject to change on the basis of continuous development.



# TWO WAY RADIOS UK

[HTTPS://TWOWAYRADIOSUK.CO.UK](https://twowayradiosuk.co.uk) 01782537000

Link House, 1880 Leek Road, Stoke on Trent, ST2 7AH



SGS certificate DE11/81829313