



TWO WAY RADIOS UK

[HTTPS://TWOWAYRADIOSUK.CO.UK](https://twowayradiosuk.co.uk)

01782537000

Link House, 1880 Leek Road, Stoke on Trent, ST2 7AH



Digital Migration Radio PD405

Digital voice, louder and clearer
Analogue & Digital Mixed Channel



Features

Private call, Group call and All call

Small, Sleek, Light

In digital mode, the radio operates up to 16 hours under a duty cycle of 5-5-90 @1500mAh.

IP55 & MIL-STD-810 C/D/E/F/G standards

Pre-programmed Text Message

Supports one touch pre-programmed text messages and voice calls.

Dual Mode (Analogue & Digital) ensures a smooth migration from analogue to digital.

DMRA Direct Mode TDMA (True 2-slot) supports two voice calls simultaneously.

Voice-operated Transmit (VOX) allows you to trigger the voice transmission by voice directly. You don't need to press the PTT button.

Analogue & Digital Mixed Channel supports automatic detecting of signal type and switching between analogue and digital modes.



Highlights

- Digital Voice, Louder and Clearer
- Double Channel Capacity
- Analogue & Digital Mixed Channel
- Easy Operation
- Durable, IP55 & MIL-STD-810 C/D/E/F/G standards
- Affordable



Target Markets



Construction

At the noisy construction site, a reliable radio with superior voice quality makes all the difference.



Warehouse

A durable battery supports full shifts without recharge.



Security

Working wirelessly makes life easier for the security worker which ultimately reduces loss.



Factory

Military standard and good dust-proof & water-proof rating (IP55) protect the radio from damage in complex environment of factory.

Standard



Options



Specifications

General	
Frequency Range	UHF: 400-470MHz, VHF: 136-174MHz
Channel Capacity	32
Zone Capacity	3
Channel Spacing	25/12.5KHz
Operating Voltage	7.4V
Battery	1500mAh (Li-Ion) 2000mAh (Li-Ion)
Battery Life (5/5/90)	Analog/Digital: 12/16 hours (1500mAh) 16/22 hours (2000mAh)
Weight	270g
Dimensions	112x54x28mm
Frequency Stability	±0.5ppm
Antenna Impedance	50Ω
Receiver	
Sensitivity (Digital)	0.22μV / BER 5%
Sensitivity (Analog)	0.22μV (Typical) (12dB SIN AD) 0.4μV (20dB SIN AD) 0.22μV (12dB SIN AD)
Adjacent Selectivity	TIA-603 60dB @ 12.5KHz/70dB @ 25KHz
	ETSI 60dB @ 12.5KHz/70dB @ 25KHz
Spurious Response Rejection	TIA-603 70dB @ 12.5/25KHz
	ETSI 70dB @ 12.5/25KHz
Inter-modulation	TIA-603 70dB @ 12.5/25KHz
	ETSI 65dB @ 12.5/25KHz
Hum & Noise	40dB @ 12.5KHz 45dB @ 25KHz
Rated Audio Power Output	0.5W
Rated Audio Distortion	≤3%
Audio Response	+1 ~ -3dB
Conducted Spurious Emission	<-57dBm

Transmitter	
RF Power Output	VHF High power: 5W VHF Low power: 1W UHF High power: 4W UHF Low power: 1W
FM Modulation	11K0F3E @ 12.5KHz 16K0F3E @ 25KHz
4FSK Digital Modulation	12.5KHz Data Only: 7K60FXD 12.5KHz Data & Voice: 7K60FXW
Conducted/Radiated Emission	-36dBm <1GHz, -30dBm >1GHz
Modulation Limiting	±2.5KHz @ 12.5KHz ±5.0KHz @ 25KHz
FM Hum & Noise	40dB @ 12.5KHz 45dB @ 25KHz
Adjacent Channel Power	60dB @ 12.5KHz, 70dB @ 25KHz
Audio Response	+1 ~ -3dB
Audio Distortion	≤3%
Digital Vocoder Type	AMBE++
Digital Protocol	ETSI-TS102 361-1,-2,-3
Environmental	
Operating Temperature	-30°C ~ +60°C
Storage Temperature	-40°C ~ +85°C
ESD	IEC 61000-4-2 (Level 4) ±8kV (Contact) ±15kV (Air)
Dustproof & Waterproof	Ip55 Standard
Humidity	Per MIL-STD-810 C/D/E/F/G Standard
Shock & Vibration	Per MIL-STD-810 C/D/E/F/G Standard

PD40X, X=0, 2, 5, 6 or 8, model number varies geographically. For details, please contact our regional sales representatives.

All specifications are subject to change without notice due to continuous development.



TWO WAY RADIOS UK

[HTTPS://TWOWAYRADIOSUK.CO.UK](https://twowayradiosuk.co.uk)

01782537000

Link House, 1880 Leek Road, Stoke on Trent, ST2 7AH



Hytera
Respond & Achieve

Hytera retains right to change the product design and specification. Should any printing mistake occur, Hytera doesn't bear relevant responsibility. Little difference between real product and product indicated by printing materials will occur by printing reason.

HYT, Hytera

©

EN20150316A